

**POTVRDA O TIPNOM ODOBRENJU**
TYPE APPROVAL CERTIFICATE**Br /No** **02-002265/024176**

Potvrđuje se da je ovaj proizvod, u skladu s Pravilima za klasifikaciju brodova, Dio 1. - Opći propisi, Odjeljak 3. - Tipno odobrenje proizvoda, odobren za ugradnju na brodove i postrojenja pod nadzorom Hrvatskog registra brodova.

This is to certify that this product, on the basis of the Rules for the classification of ships, Part 1 - General requirements, Chapter 3 - Type approval of products, is approved for use on board ships and installations under supervision of the Croatian Register of Shipping.

TIP I OPIS PROIZVODA:*TYPE AND DESCRIPTION OF PRODUCT:***DIZELSKI MOTOR, tip DI09 M**
DIESEL ENGINE, type DI09 M**PROIZVOĐAČ:**
MANUFACTURER:**SE-151 87 Södertälje**
Sweden**PROIZVOD UDOVOLJAVA SLJEDEĆIM PRAVILIMA/PROPISIMA:**
*THE PRODUCT MEETS FOLLOWING RULES/REGULATIONS:***HRB: Pravila za klasifikaciju brodova, Dio 9. - Strojevi.**
*CRS: Rules for the classification of ships, Part 9. - Machines.***DETALJI O PROIZVODU I UVJETIMA CERTIFIKACIJE DANI SU NA POLEĐINI.**
*FURTHER DETAILS OF THE PRODUCT AND CONDITIONS FOR CERTIFICATION ARE GIVEN OVERLEAF.***ODOBRENJE VRIJEDI DO:** **2021-09-12**
*APPROVAL IS VALID UNTIL:***Mjesto i datum:** **Split, 2017-08-07**
*Place and date:***M.P.**
*(Seal)***Marinko Popović, dipl.ing.**

NAPOMENA: Ova potvrda nije valjana ako se proizvod ili način njegove proizvodnje promijenio u odnosu na tipno ispitani proizvod. Proizvođač treba obavijestiti Hrvatski registar brodova o bilo kojoj izmjeni na proizvodu kako bi ishodio valjanu potvrdu.

NOTE: This certificate is not valid for equipment, the design or manufacture of which has been varied or modified from the specimen tested. The manufacturer should notify Croatian Register of Shipping of any modification or changes to the product in order to obtain a valid certificate.

PODROBNJI OPIS PROIZVODA:
DETAILED PRODUCT DESCRIPTION:

4-taktni, jednoradni dizel motor

4-stroke, single acting diesel engine

Promjer cilindra: 130 mm

Cylinder bore: 130 mm

Hod klipa: 140 mm

Piston stroke: 140 mm

Broj cilindara: 5(L)

Cylinder number: 5(L)

PODRUČJE PRIMJENE / POSEBNI GRANIČNI UVJETI:
APPLICATION / LIMITATIONS:

Nazivna trajna snaga / MCR (kW)	Brzina vrtnje / speed (rpm)	Namjena / service
257	1800	propulsion
294	2100	propulsion
269	1500	auxiliary / emergency
323	1800	auxiliary / emergency

Motore za pomoćne namjene i nužnost moguće je preopteretiti za 10% snage.

Engines in auxiliary and emergency service are over loadable with 10% of power.

DOKUMENTACIJA ZA TIPNO ODOBRENJE:
TYPE APPROVAL DOCUMENTATION:

Nacrti i proračuni odobreni od HRB dopisom:

1998/TS/IA/023494 (2013-09-12)

Drawings and calculations approved by CRS with letter:

OZNAČAVANJE PROIZVODA:
MARKING OF PRODUCT:

- | | |
|--|---|
| - oznaka proizvođača | - <i>manufacturer's mark</i> |
| - mjesto i godina završne montaže | - <i>location and year of final fitting</i> |
| - oznaka HRB | - <i>CRS mark</i> |

UVJETI ZA CERTIFIKACIJU:
CONDITIONS FOR CERTIFICATION:

Najmanja rastezna čvrstoća materijala koljenastog vratila je 850 MPa.

Signalizacija i zaštita vezana za motor bit će od slučaja do slučaja stvar posebnog odobrenja HRB, a ovisit će o namjeni motora i stupnju automatizacije motornog postrojenja.

Proračun torzijskih vibracija mora biti dostavljen za svaku instalaciju na osnovi Pravila HRB.

Minimal tensile strength of crankshaft material is 850 MPa.

Signalization and protection related to the engine shall be subject to CRS approval in each particular case and will depend on service applied and the degree of automation of the engine plant.

Torsional vibration calculation shall be submitted for each installation in accordance with the Rules of CRS.